









Features		models
	1280A	1275
Color Bars	V	<ul> <li>✓</li> </ul>
Black Raster	V	
Color Rasters	V	V
Window	V	
Dot	V	<ul> <li>✓</li> </ul>
Crosshatch	V	<ul> <li>✓</li> </ul>
Multiple Outputs	V	
RGB	V	
H/HV Sync	V	
V Sync	V	
Auto/Manual	V	<ul> <li>✓</li> </ul>
Gray scale	V	
Available Patterns		
PC:1280 x 1024	V	<ul> <li>✓</li> </ul>
1024 x 768	V	<ul> <li>✓</li> </ul>
(non-interlaced)		
8415A (interlaced)	V	~
SVGA 800 x 600	V	<ul> <li>✓</li> </ul>
SVGA 1024 x 768	V	<ul> <li>✓</li> </ul>
VGA 640 x 480	<ul> <li>✓</li> </ul>	<ul> <li>✓</li> </ul>
VGA 640 x 350	<ul> <li>✓</li> </ul>	
VGA 720 x 400	<ul> <li>✓</li> </ul>	
EGA	<ul> <li>✓</li> </ul>	V
CGA	<ul> <li>✓</li> </ul>	V
MDA	V	
Mac:1280 x 1024	V	
1152 x 870	V	
1024 X 768	<ul> <li>✓</li> </ul>	
(non-interlaced)		
832 x 624	V	
640 x 480	V	V
512 x 384	<ul> <li>✓</li> </ul>	
Power Source	9V battery or	
Dimensions	3.125 x 9.44 x 9.25"	1.5 x 3.8 x 5.7"
	(78 x 240 x 235mm)	(38 x 97 x 145n
Weight	2.5lbs. (1.1kg)	0.5 lbs. (227g)

SUPPLIED:	BE-12 AC adapter	9V battery
OPTIONAL:		BE-12 AC adapter





## Model 1280A

The 1280A is a fully featured bench-top design to test both Mac and PC monitors. All patterns can be manually selected or place the 1280A in Auto for automatic cycling of each available pattern. Designed to test (burn-in) one to four monitors, the 1280A can also be used as a display generator. Full color, green, blue, red, black and white.

1275

- PC and Mac Patterns
- 16 Monitor Types/Resolution Selections
- Color bar, Cross Hatch, Dot, Raster, Windows<sup>®</sup> selection
- VGA, SVGA, RGB, HV,V & Four DB-15 (Rear panel) for multiple monitor burn-in

## Model 1275

Great handheld unit to test PC and Mac monitors. The model 1275 is ideal for the field or the service bench. Small, portable and very effective, the 1275 generates crosshatch, dots, color bars and raster patterns in green, blue, red, black and white.

## ∎ CGA, VGA, SVGA

Standard DB-9, DB-15 and DB-15 Hi-res mini connectors

Calle del Ebano #16625 Jardines de Chapultepec Tijuana B.C. Mexico Tel. (664) 681 1130 Fax. (664) 681 1150 Tel. 01800 027-4848