

# HIOKI

**New**

## 3246 PENCIL HiTESTER

Field measuring instruments



Penlight



# Ultra Bright



Backlight LCD



ISO14001  
JQA-E-90091



<http://www.hioki.co.jp/>

HIOKI company overview, new products, environmental considerations and other information are available on our website.

CE


# Smart Design and Ease of use




Backlight LCD is highly visible, even in dark locations

Penlight brightly illuminates test points

◆ 600 V circuit protection makes fuses unnecessary




◆ Comes with protective probe tip cap



Actual-size

◆ Test lead fits neatly into back of instrument



## Specifications (Accuracy at 23°C ± 5°C (73°F ± 9°F), 80% rh or less)

Function	Range (Accuracy)
<b>DC voltage</b>	420.0 m / 4.200 / 42.00 / 420.0 / 600 V (± 1.3 %rdg. ± 4 dgt.)
<b>AC voltage</b> (50 to 500 Hz)	4.200 / 42.00 / 420.0 / 600 V (± 2.3 %rdg. ± 8 dgt.)
<b>Resistance</b> (open terminal voltage 3.4 V max.*1)	420.0 / 4.200 k / 42.00 k / 420.0k / 4.200 M / 42.00 MΩ (± 2.0 %rdg. ± 4 dgt.*2)
<b>Continuity</b> (open terminal voltage 3.4 V max.)	420.0 Ω (± 2.0 %rdg. ± 4 dgt.) Buzzer sounds at approx 50 Ω ± 30 Ω or less
<b>Diode test</b> (open terminal voltage 3.4 V max.)	Forward direction identification function*3 Indicator flashes and buzzer sounds to indicate forward direction

\*1. at 420 Ω. (4.2 k 0.7 V (typ.) 42 k to 42 M 0.5 V (typ.))

\*2. at 420 to 420 kΩ. (4.2 MΩ ± 5.0 %rdg. ± 4 dgt. 42 MΩ ± 10.0 %rdg. ± 4 dgt.)

\*3. Works when diode has a forward voltage from 0.3 V to 2.0 V

● Measurement system: average value rectification ● Display: Max.4199-count LCD ● Range switching: automatic or manual ● Ancillary functions: data hold function, auto power save function, battery life warning function, penlight, backlight LCD ● Sampling rate: 2.5 times/sec ● Overload protection: 600 Vrms (sin) or 3 × 10<sup>6</sup> VHz for all functions ● Applicable standards: Safety - EN61010 CAT III 600V, EMC - EN61326 ● Ambient temperature of use: 0 to 40°C (32°F to 104°F), 80%rh (no condensation) ● Storage temperature range: -20 to 60°C (-4°F to 140°F), (no condensation) ● Power source: CR2032 battery × 1 (3V DC) ● Continuous operating time: approx. 150 h (During DC voltage measurement), approx. 30 h (During DC voltage measurement, assuming 10 sec illumination alternating with 20 sec dark) ● Dimensions and mass: Approx. 30 W × 182 H × 26.5 D mm, 80 g (Approx 1.2" (W) × 7.2" (H) × 1.0" (D), 2.8 oz.)

## 3246 PENCIL HiTESTER

Option

9081 10 A SHUNT (output: 100 mV / 10 A)

# HIOKI

HIOKI E. E. CORPORATION

### HEAD OFFICE :

81 Koizumi, Ueda, Nagano, 386-1192, Japan  
TEL +81-268-28-0562 / FAX +81-268-28-0568  
E-mail: os-com@hioki.co.jp

### HIOKI USA CORPORATION :

6 Corporate Drive, Cranbury, NJ 08512 USA  
TEL +1-609-409-9109 / FAX +1-609-409-9108  
E-mail: hioki@hiokiusa.com

### Europe Representative Office :

Meineckestrasse 48, 40474 Dusseldorf, Germany  
TEL / FAX +49-211-4544153  
E-mail: hioki-eu@doitsu.de

### Shanghai Representative Office :

1108 Union Building, 100 Yan An Road (East),  
Shanghai, 200002, P.R.China  
TEL +86-21-6328-9947/4938  
FAX +86-21-6328-2064  
E-mail: hioki-sh@sh.cngb.com

DISTRIBUTED BY

## FINAL TEST<sup>MR</sup>

Venta de Instrumentos de Prueba y Medición

Calle del Ebano #16625  
Jardines de Chapultepec  
Tijuana B.C. Mexico  
Tel. (664) 681 1130  
Fax. (664) 681 1150  
Tel. 01800 027-4848  
www.finaltest.com.mx