

Datos técnicos

## Pozos manos secos 9102 de Fluke Calibration



### Características principales

World's smallest, lightest and most portable dry-wells

- Smallest dry-wells in the world
- Ranges from  $-10^{\circ}\text{C}$  to  $122^{\circ}\text{C}$
- Accuracy to  $\pm 0.25^{\circ}\text{C}$ , stability of  $\pm 0.05^{\circ}\text{C}$
- RS-232 interface
- Fluke Calibration's line of portable dry-wells is incredible. They're the smallest, lightest, and most portable dry-wells in the world. And now they're better than ever!

### Descripción general del producto: Pozos manos secos 9102 de Fluke Calibration

#### 9102S Dry-Well

For work in the temperature range of  $-10^{\circ}\text{C}$  to  $122^{\circ}\text{C}$ , 9102S dry-well is another first in the industry, featuring stability to  $\pm 0.05^{\circ}\text{C}$ .

This dry-well is only four inches high and six inches wide, achieves temperatures as low as  $-10^{\circ}\text{C}$ , includes a NIST-traceable calibration, and is stable to  $\pm 0.05^{\circ}\text{C}$ . The Model 9102S is excellent for dial gauges, digital thermometers, bulb switches, and other sensors that need calibration below ambient.

The 9102S has two wells so you can use one for a reference thermometer to increase accuracy. Both wells are 1/2 inch in

diameter, and each has inserts available for almost any sensor size. The 9102S also has a battery pack option that gives you approximately four hours of field use when AC power is unavailable.

## Especificaciones: Pozos manos secos 9102 de Fluke Calibration

Specifications	9100S	9102S
<b>Range</b>	35 °C to 375 °C (95 °F to 707 °F)	-10 °C to 122 °C (14 °F to 252 °F) at 23 °C ambient
<b>Accuracy</b>	± 0.25 °C at 50 °C; ± 0.25 °C at 100 °C; ± 0.5 °C at 375 °C	± 0.25 °C
<b>Stability</b>	± 0.07 °C at 50 °C; ± 0.1 °C at 100 °C; ± 0.3 °C at 375 °C	± 0.05 °C
<b>Well-to-Well Uniformity</b>	± 0.2 °C with sensors of similar size at equal depths within wells	
<b>Heating Times</b>	35 °C to 375 °C: 9.5 minutes	ambient to 100 °C: 10 minutes
<b>Stabilization</b>	5 minutes	7 minutes
<b>Cooling Times</b>	375 °C to 100 °C: 14 minutes	ambient to 0 °C: 10 minutes
<b>Well Depth</b>	102 mm (4 in); 1.6 mm (1/16 in) hole is 89 mm (3.5 in) deep	102 mm (4 in)
<b>Removable Inserts</b>	N/A	Available in sizes from 1.6 mm (1/16 in) to 11.1 mm (7/16 in) [6.4 mm (1/4 in) and 4.8 mm (3/16 in) included]
<b>Power</b>	115 V ac (± 10 %), 55–65 Hz, 1.5 A or 230 V ac (± 10 %), 0.8 A, 45–55 Hz, 175 W	94–234 V ac (± 10 %), 50/60 Hz, 60 W; or 12 VDC
<b>Size (HxWxD)</b>	57 x 125 x 150 mm (2.25 x 4.9 x 6.1 in)	99 x 140 x 175 mm (3.9 x 5.5 x 6.9 in)
<b>Weight</b>	1 kg (2 lb 3 oz)	1.8 kg (4 lb)
<b>Computer Interface</b>	RS-232 included	
<b>NIST-Traceable Calibration</b>	Data at 50 °C, 100 °C, 150 °C, 200 °C, 250 °C, 300 °C, and 375 °C	Data at -10 °C, 0 °C, 25 °C, 50 °C, 75 °C, 100 °C, and 122 °C

## Modelos



### **Fluke 9102S-156**

9102S-156, DRY-WELL, HH LOW-TEMP

---

**Fluke.** *Manteniendo su mundo en marcha.*

**Fluke Corporation**  
Everett, WA 98206 EE.UU.

**Para obtener información adicional En EE. UU. (800) 443-5853**

**En Europa/Medio Oriente/África**  
**+31 (0)40 267 5100**

**En Canadá (800)-36-FLUKE**  
**[www.fluke.com](http://www.fluke.com)**

**Latin America**  
Tel: +1 (425) 446-5500  
[www.fluke.com/laam](http://www.fluke.com/laam)

©2023 Fluke Corporation. Reservados todos los derechos. Impreso en los Países Bajos. Información sujeta a modificación sin previo aviso.  
04/2023

**No está permitido modificar este documento sin autorización por escrito de Fluke Corporation.**