

Comprehensive Data Logger

20 channel Portable Logger

mini LOGGER GL820

Voltage Temp. Humidity Pulse Logic



20CH Fast Sampling 10ms Wide LCD 5.7inch



20 insulated channels, each with multifunction input capacity

Contains an insulated input system which ensures signals do not cause any distortions among other channels. Suitable for recording voltage, temperature, humidity, pulse, and logic signals.


- Voltage** 20mV to 50V wide range
- Temp.** Supported 9 type of thermocouples: R, S, B, K, E, T, J, N, W
- Humidity** Measured the humidity easily using the optional sensor
- Pulse** Supports 4 channels pulse or logic digital I/O using optional cable B-513.
- Logic**

Built-in 2GB Flash memory for reliable long term measurement

The 2GB Flash Memory enables a secure long term data measurement usage without applying an external storage device.

Supports USB memory with Real-Time Swaps

Supports USB 2.0 memory sticks for external storage. The GL820 saves measured data directly on to the USB memory sticks. The device can be replaced during measurement without losing any data.



Maximum 10ms Sampling

Provides faster sampling rates for voltage measurements. Achieves up to 10ms sampling interval when limiting the number of channels in use.

5.7 inch TFT colour LCD

Utilises an industry leading 5.7-inch TFT color LCD monitor (VGA: 640 x 480 dots). Providing enhanced ability to read data in waveform and digital forms to measure and analyze data in real time.

Ring memory function

The most recent data is saved when internal memory or external memory is configured in ring memory mode.

GL820 main unit specifications		
Item	Description	
Number of analog input channels	20 ch, Expandable up to 200 ch by unit of 20 ch	
External input output	Input ^{*8}	Trigger or Sampling input 1 ch, Logic or Pulse input 4 ch
	Output ^{*8}	Alarm output 4 ch
Sampling interval	10 ms to 1 h (in 10ms to 50ms, voltage only and limited channel), External	
Time scale	1 sec to 24 hour /division	
Trigger function	Action	Start or stop capturing data by the trigger
	Source	Start: O ff, Input signal, Alarm, External ^{*8} , Clock, Week or Time Stop: O ff, Input signal, Alarm, External ^{*8} , Clock, Week or Time
	Combination	OR or AND condition at the level of signal or edge of signal
	Condition	Analog: Rising, Falling, Window-in, Window-out
		Pulse: Rising, Falling, Window-in, Window-out Logic: Rising, Falling
Alarm function	Detecting method	Level or edge of signal
	Condition	Analog: Rising, Falling, Window-in, Window-out Pulse: Rising, Falling, Window-in, Window-out Logic: Rising, Falling
	Alarm output ^{*8}	4 channels, Output type: Open collector (pulled-up to 5 V by resistor 10 kΩ)
Pulse input function ^{*8}	Accumulating count mode	Accumulating the number of pulses from the start of measurement Range: 50, 500, 5 k, 50 k, 500 k, 5 M, 50 M, 500 M counts/ F.S.
	Instant count mode	Counting the number of pulses per sampling interval Range: 50, 500, 5 k, 50 k, 500 k, 5 M, 50 M, 500 M counts/ F.S.
	Rotation count (RPM) mode	Counting the number of pulses per second and then it is converted to RPM Range: 50 rpm, 500 rpm, 5 krpm, 50 krpm, 500 krpm, 5 Mrpm, 50 Mrpm, 500 Mrpm / F.S.
	Max. input pulse rate	50 k pulses/sec or 50k counts per sampling interval (16 bits counter is used)
	Between channels	Addition, Subtraction, Multiplication and Division for analog input
Calculation function	Statistical	Select two calculations from Average, Peak, Max., Min., RMS
	Search function	Search for analog signal levels, values of logic or pulse or alarm point in captured data
Interface to PC	Ethernet (10 BASE-T/100 BASE-TX), USB (Full speed)	
Storage device	Built-in Flash memory (2 giga-bytes), USB memory device ^{*9}	
Data saving function	Captured data	Direct saving of data into built-in Flash memory or USB memory device
	Others	Setting conditions, Screen copy
Ring capturing mode	Function: ON/OFF, Number of capturing point: 1000 to 2000000 (size of the capture data will be limited to 1/3 of available memory when in Ring Mode)	
USB memory device emulation	USB Memory emulation mode (Transfer or delete the file in built-in memory)	
Engineering scale function	Set based on the reference point of the scaled output and input signal for each channel (Voltage measurement: four points are necessary to scale the output, Temperature measurement: two points are necessary to scale the output).	
Display	Size	5.7 inch TFT color LCD (VGA: 640 x 480 dots)
	Formats	Waveform + Digital, Waveform only, Calculation + Digital, Expanded digital
Operating environment	0 to 45 °C, 5 to 85 %RH (When operating with battery pack 0 to 40 °C, charging battery 15 to 35 °C)	
Power source	AC adapter (100 to 240 V, 50/60 Hz), DC power (8.5 to 24 V DC, max. 26.4 V) ^{*10} , Battery pack ^{*10}	
Power consumption	32 VA or lower (when operating with AC adapter, displaying LCD, charging battery pack)	
External dimensions (WDDH)	approx. 232 x 152 x 50 mm	
Weight	approx. 900 g (Excluding AC adapter and battery pack)	

Software specifications


Item	Description
Supported OS	Windows X P / Vista / 7 (32 bits and 64 bits edition)
Functions	Control GL820, Real-time data capture, Replay data, Data format conversion
GL820 settings control	Input settings, Memory settings, Alarm settings, Trigger settings
Controlled units	Up to 10 units or 500 channels
Captured data	Transfers data in real-time (in binary or CSV format), saved data in GL820 or the USB memory
Displayed information	Analog waveforms, Logic waveforms, Pulse waveforms, Digital values
Display modes	Y-T waveforms, Digital values, Report, X-Y graph (specified period of data, data reply only)
Warning functions	Sends E-mail to the specified address when the alarms occur
File format conversions	Converts the specified period data or all data to the CSV format (thinning function is available)
Report functions	Creates the daily or monthly report automatically (can also export directly to Excel)

Standard accessories

Item	Description	Quantity
AC adapter	100 to 240 V AC, 50 / 60 Hz (with specified type of power cord)	1 set
CD-ROM	User's manual (PDF format), Application software	1 piece
Quick Start Guide		1 copy

Options and accessories

Item	Model number	Remarks
Logic alarm cable	B-513	2 m long (no clip on end of cable)
DC drive cable	B-514	2 m long (no clip on end of cable)
Battery pack	B-517	1 piece (7.4 V 2200 mAh, 17Wh)
Humidity sensor ^{*12}	B-530	3 m long (with power plug)
Extension terminal base kit	B-537	Terminal base, cable
20 ch extension terminal set	B-538	Terminal base, terminal unit (20 ch), fixing plate



^{*12}: Operating environment: -25°C to 80°C

Analog input specifications

Item	Description					
Type of input terminal	Screw terminal (M3 screw)					
Input method	Scans by the photo-MOS-relay, all channels isolated, balanced input					
Measurement range	Voltage	20, 50, 100, 200, 500 mV, 1, 2, 5, 10, 20, 50V, and 1-5 V/ F.S.				
	Temperature	Thermocouple: K, J, E, T, R, S, B, N, and W (WRe5-26) Resistance Temperature Detectors (RTDs): Pt100, JPt100(JIS), Pt1000(IEC751)				
	Humidity	0 to 100% (using humidity sensor or (B-530 optional), power is supplied to only one sensor)				
Filter	Off, 2, 5, 10, 20, 40 (moving average in selected number)					
Measurement accuracy ^{*11}	Voltage Temperature	Thermocouple	Measurement range	Measurement accuracy		
		R/S	0 °C ≤ TS ≤ 100 °C	± 5.2 °C		
			100 °C < TS ≤ 300 °C	± 3.0 °C		
			R: 300 °C < TS ≤ 1600 °C	± (0.05 % of reading + 2.0 °C)		
			S: 300 °C < TS ≤ 1760 °C	± (0.05 % of reading + 2.0 °C)		
			B	400 °C ≤ TS ≤ 600 °C	± 3.5 °C	
		600 °C < TS ≤ 1820 °C		± (0.05 % of reading + 2.0 °C)		
		K	-200 °C ≤ TS ≤ -100 °C	± (0.05 % of reading + 2.0 °C)		
			-100 °C < TS ≤ 1370 °C	± (0.05 % of reading + 1.0 °C)		
		E	-200 °C ≤ TS ≤ -100 °C	± (0.05 % of reading + 2.0 °C)		
			-100 °C < TS ≤ 800 °C	± (0.05 % of reading + 1.0 °C)		
		T	-200 °C ≤ TS ≤ -100 °C	± (0.1 % of reading + 1.5 °C)		
			-100 °C < TS ≤ 400 °C	± (0.1 % of reading + 0.5 °C)		
		J	-200 °C ≤ TS ≤ -100 °C	± 2.7 °C		
			-100 °C < TS ≤ 100 °C	± 1.7 °C		
			100 °C < TS ≤ 1100 °C	± (0.05 % of reading + 1.0 °C)		
		N	0 °C ≤ TS ≤ 1300 °C	± (0.1 % of reading + 1.0 °C)		
		W	0 °C ≤ TS ≤ 2000 °C	± (0.1 % of reading + 1.5 °C)		
		Reference Junction Compensation (R.J.C.): ±0.5 °C				
		RTD			Measurement range	Measurement accuracy
		Pt100			-200 °C to 850 °C (FS = 1050 °C)	± 1.0 °C
JPt100			-200 °C to 500 °C (FS = 700 °C)	± 0.8 °C		
Pt1000			-200 °C to 500 °C (FS = 700 °C)	± 0.8 °C		
A/D Converter	ΣΔ type, 16 bits (effective resolution: 1/40000 of measuring full range)					
Maximum input voltage	Between + / - terminal	60 V p-p				
	Between channels	60 V p-p				
	Between channel / GND	60 V p-p				
Withstand voltage	Between channels	350 V p-p (1 minute)				
	Between channel(-) / GND	350 V p-p (1 minute)				

^{*8} : Logic alarm cable (B-513) option is required.

Input signal of External sampling, Logic, Pulse; Maximum voltage: 24V Threshold: approx. 2.5V, Hysteresis: approx. 0.5V

^{*9} : Size of the USB memory device is unlimited. Maximum file size is limited to 2GB.

^{*10}: DC drive cable (B-514) or battery pack (B-517) option is required.

^{*11}: Subject to the following conditions;

- Room Temperature is 23°C ±5°C.
- When 30 minutes or more have elapsed after power was turned on.
- Filter is set to 10.
- Sampling rate is set to 1s with 20 channels.
- GND terminal is connected to ground.

Brand names and product names listed in this brochure are the trademarks or registered trademarks of their respective owners. Specifications are subject to change without notice.

GRAPHTEC

GRAPHTEC AMERICA, INC.

17462 Armstrong Avenue
Irvine, CA 92614

Website

<http://www.graphtecamerica.com>

