



## WT-10 PH / mV Pen-Type Water Quality Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy to use, one touch water management testers. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- PH ranges from 0 to 14
- Dual LCD display with pH and temperature (selectable C and F)
- Simple one-touch auto-calibration
- Easy to read 45° ANGLE display
- Replaceable pH electrode
- Automatic Temperature Compensation assures that readings are corrected for temperature offsets
- In-field calibration up to 3 points (pH 4.00, 7.00, 10.00)
- Waterproof and dustproof - IP66
- Portable design with pocket clip
- Probe easy to replace and assemble
- No tools or trimmers needed for calibration
- Meter includes battery and manual in a gift box
- Wide range of application: Pools, Aquariums, Labs, Aquaculture, Car washes, Water testing and Waste water treatment
- Hold Record
- Disable Sleep mode
- Low battery indicator
- Nylon bag supplied with a product

### No hassle warranty

*No waiting.*

*No shipping charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

**WT-10 PH/mV Pen-Type Water Quality Meter****Data Sheet****Specifications**

<b>PH Range</b>	0.00~14.00 ( $\pm 0.01$ pH)
<b>pH Accuracy</b>	$\pm 0.05$ pH
<b>Temperature Compensation</b>	0°C to 50°C (32°F to 122°F)
<b>Temp. Accuracy</b>	$\pm 0.5^\circ\text{C}$ ( $\pm 31.1^\circ\text{F}$ to $32.9^\circ\text{F}$ )
<b>Display</b>	4 digit
<b>Operating Temperature</b>	0°C to 50°C (32°F to 122°F)
<b>Operating Humidity</b>	0-80%RH
<b>Auto Power Off</b>	20 minutes
<b>Dimension</b>	149 x 37 x 42 mm (5.9 x 1.5 x 1.7 in)
<b>Weight</b>	Approx. 76g (0.17 lb)