### **Botron B6223 Technical Data Sheet**

# BOTRON

#### Overview:

Type T2 rubber table mats dual layer design provide excellent electricals and durability. It exceeds both EOS/ESD and Department of Defense requirements. Available in Blue, Gray and Green rolls, and pre-cut table mats with hardware.

PROPERTIES	SPECIFICATIONS
Material:	.060" Thick Rubber Construction Dissipative top layer
Meets Standards:	Conductive bottom layer ANSI EOS/ESD S4.1 RTG ANSI EOS/ESD S4.1 RTG
Electricals:	Fed Std 101 Method 4046 Top Layer 108 Conductive Back Layer 104 RTT (Resistance Top to Top) 5.8×107- 6×108 Ohms Resistance to Ground 5.2×107- 5×108 Ohms Charge Decay Time
Colors:	5000 volts to 50v <0.01 Seconds Blue, Gray, Green

#### **AVAILABLE APPLICATIONS**

50' runners Standard and Custom Cut Table Mats

## FRAL TEST Venta de Instrumentos de Prueba y Medición

Calle del Ebano #16625 Jardines de Chapultepec

Jardines de Chapultepec Tijuana B.C. Mexico Tel. (664) 681 1130 Fax. (664) 681 1150 Tel. 01800 027-4848 www.finaltest.com.mx

#### **Product Notes and Features**

- Dual-Layer Design
- Superior Electricals
- Resistant to Hot Solder
- Conductive Bottom Layer
- Non-Skid Backing
- Reversable from Dissipative to Conductive
- Chemical and Abrasion Resistant
- Compatible with Constant Monitors
- Embossed Paper Finish
- Lead-Free RoHS Compliant



#### INSTALLATION

- 1. Remove mat from bag.
- 2. Attach 10' common point ground B9702 to 3/8" snap on mat.
- 3. Connect opposite end of wire to ground.
- 4. Check with your facility people for building ground.

#### **GROUNDING**

All pre-cut mats come with attached snap and one B9703 common point ground. B9703 when properly setup will ground the mat and provide ground points for two workers via standard banana jack. For grounding rolls please see hardware (each mat will need a snap and ground to be effective).

#### **TESTING GUIDELINES**

Botron recommends testing ESD mats with the following test equipment: B8582, B8572, B8563, B8560, BSRM6, BSRM10.

Using two 5lbs. weights, placing them approximately 18" apart, conduct the test according to the test equipment which you are using.

Conduct this test to achieve a reading for RTG (resistance to ground) and RTT (resistance top to top) respectively.

When using the BSRM6 and BSRM10, simply place on top of surface of mat and hold down test button to achieve a surface resistance reading.

\*Please note, it is recommended to read the testing guidelines provided with the ESD Tester you are using.

#### PART NUMBERS

Blue ESD Rubber Mat

B6123 2' x 3' 2 layer blue mat w/snap and ground

B6124 2' x 4' 2 layer blue mat w/snap and ground

B6125 2' x 5' 2 layer blue mat w/snap and ground

B61304 30" x 4' 2 layer blue mat w/snap and ground

B61250 2' x 50' blue 2 layer roll

B61350 3' x 50' blue 2 layer roll

B61450 4' x 50' blue 2 layer roll

B613050 30" x 50' blue 2 layer roll

#### Green ESD Rubber Mat

B6223 2' x 3' 2 layer green mat w/snap and ground

B6224 2' x 4' 2 layer green mat w/snap and ground

B6225 2' x 5' 2 layer green mat w/snap and ground

B62304 30" x 4' 2 layer green mat w/snap and ground

B62250 2' x 50' green 2 layer roll

B62350 3' x 50' green 2 layer roll

B62450 4' x 50' green 2 layer roll

B623050 30" x 50' green 2 layer roll

#### Gray ESD Rubber Mat

B6423 2' x 3' 2 layer gray mat w/snap and ground

B6424 2' x 4' 2 layer gray mat w/snap and ground

B6425 2' x 5' 2 layer gray mat w/snap and ground

B64304 30" x 4' 2 layer gray mat w/snap and ground

B64250 2' x 50' gray 2 layer roll

B64350 3' x 50' gray 2 layer roll

B64450 4' x 50' gray 2 layer roll

B643050 30" x 50' gray 2 layer roll

Botron Company Inc. | 325 W. Melinda Ln Phoenix AZ 85027 Ph# 623-582-6700 | Fax# 623-582-6776

**Disclaimer.** All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user. The statements herein shall have no force or effect.