



FEATURES:

- ✓ Provides a quick and easy means of shorting two inputs of a miniature double banana jack.
- ✓ The plug to plug and jack to jack dimension is .500" (12,70mm) which is typical for double miniature banana plugs/jacks.
- ✓ ABS body provides insulation protection to the user.
- ✓ Shorting adapter has double miniature jacks at the topside for stacking capability.

MATERIALS:

Miniature Double Banana Jack

Body: Gold Plated Brass

Miniature Double Banana Plug

Body: Gold Plated Brass

Spring: Gold Plated Beryllium Copper

Insulation: ABS molded to banana plug and jack bodies

RATINGS:

Operating Voltage: Hands free usage in controlled voltage environments: 2500 Vrms maximum. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

Current: 5 Amperes

Operating Temperature: +122°F (+50°C) Max.

ORDERING INFORMATION:

Model 2035-0 (Black)

Model 2035-2 (Red)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Distribuido Por:

www.finaltest.com.mx
 Calle del Eban #16625
 Tijuana B.C. Mexico
 Tel. (664)681-1130
 Tel. 01800 027-4848
 ventas@final-test.net