



#### **FEATURES:**

- ✓ Hermetically sealed: Leakage rate less than  $10^{-7}$  cc/sec of tracer gas at one atmosphere.

#### **MATERIALS:**

Body and Fittings: Brass, Tarnish Resistant Nickel Plated Brass

Center Contact: Gold Plated Beryllium Copper

Dielectric: PTFE

#### **RATINGS:**

Operating Voltage: Hands free usage in controlled voltage environments: 500 Vrms maximum. *For CE compliance: not intended for hand-held use at voltages above 33 Vrms/70 Vdc.*

Operating Temperature: -65°C to +165°C

Nominal Impedance: 50 Ohms

#### **ORDERING INFORMATION:**

Model 3847

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02$ " (.51 mm), .xxx =  $\pm .005$ " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Distribuido Por:

[www.finaltest.com.mx](http://www.finaltest.com.mx)

Calle del Ebanó #16625

Tijuana B.C. Mexico

Tel. (664)681-1130

Tel. 01800 027-4848

[ventas@final-test.net](mailto:ventas@final-test.net)