



FEATURES:

- Replaceable tip probe set with sharp stainless steel tip included. (Other tips are available, see model 6475.)
- Designed for DMM's with non-sheathed banana jacks
- Also fits new DMM's with safety-sheath banana jacks
- Thermoplastic elastomer outer coat provides comfortable grip and flexible strain relief
- Probe and banana plug are molded directly to the wire for robust pull strength
- Wire is a high-strand count silicone wire for extreme flexibility and high temperature resistance
- An oversized shoulder allow easy connect and disconnect
- Mates to any standard banana jack

MATERIALS:

Probe:

Outer Insulation: Santoprene® rubber, color: gray

Inner Insulation: polypropylene, color: one black, one red

Tip: stainless steel

Wire: 18 AWG

Banana Plug: Nickel-plated Brass

Spring – Nickel-plated Beryllium Copper

Plug Insulation: polypropylene, color: one black, one red

RATINGS:

Operating Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 1000 VRMS Max.

Current: 5 Amperes Max.

ORDERING INFORMATION: Model 5951A

Includes a set of one black and one red test lead with two replaceable tips.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Distribuido Por:

www.finaltest.com.mx

Calle del Eban #16625

Tijuana B.C. Mexico

Tel. (664)681-1130

Tel. 01800 027-4848

ventas@final-test.net

FINAL TEST[™]
Venta de Instrumentos de Prueba y Medición