



#### FEATURES:

- ✓ Shielded cable to reduce noise.
- ✓ Bantam Plugs molded to the cable to provide optimum durability.

#### MATERIALS:

Plugs: Nickel Plated Brass.  
 Main Cable: 4 Conductor Shielded Twisted Pair.  
 Breakout Cables: 2 Conductor Shielded Twisted Pair.  
 Wire Jackets and Insulators: PVC  
 Breakout: Molded PVC

#### RATINGS:

Voltage: Hands free usage in controlled voltage environments: 300 Vrms Max. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.  
 Current: 0.5 Amperes per conductor @ 25°C Max.  
 Operating Temperature: -4°F to +176°F (-20°C to +80°C)

#### ORDERING INFORMATION: Model 6320-96

Standard Length: 96" Inches (2,43M)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
 All specifications are to the latest revisions. Specifications are subject to change without notice.  
 Registered trademarks are the property of their respective companies.

Distribuido Por:  
 www.finaltest.com.mx  
 Calle del Ebano #16625  
 Tijuana B.C. Mexico  
 Tel. (664)681-1130  
 Tel. 01800 027-4848  
 ventas@final-test.net