

Model 6733, 6734 Test Lead Wire with Silicone or PVC Insulation

Features:

- ✓ Same wire as used with the Pomona test leads and patch cords.
- ✓ Make your own "Extra Long" test leads, jumpers or patch cords.
- ✓ Fits Pomona "Do-It-Yourself" banana plugs and jacks.
- ✓ High temperature and voltage ratings.
- ✓ Silicone insulation with high wire strand count allows for superb flexibility.
- ✓ Wire will comply with International Safety Standard CAT III, IEC1010 requirements when correctly terminated with other components designed to meet CAT III, IEC1010 requirements.



6733	6734
Silicone	PVC
50 FT (15,2 meters)	50 FT (15,2 meters)
18 AWG	18 AWG
65 X 36 tinned copper	65 X 36 tinned copper
.144" (3,60mm)	.144" (3,60mm)
-58 to +302 F (-50 to +150 C)	-4 to +221 F (-20 to +105 C)
10,000 DC *	5,000 DC *
20 A	15 A
6733-0	6734-0
6733-2	6734-2
	Silicone 50 FT (15,2 meters) 18 AWG 65 X 36 tinned copper .144" (3,60mm) -58 to +302 F (-50 to +150 C) 10,000 DC * 20 A

^{*} Hands free testing in controlled voltage environment: *For CE compliance:* not intended for hand held use at voltages above 33 Vrms / 70 Vdc.

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

