



OMNIA®

Fully-Automated, Multi-Function Electrical Safety Compliance Analyzer

Multi-function safety compliance analyzers with an enhanced graphic LCD provide complete test setup and results in an easy-to-use interface. OMNIA® provides 4-in-1, 5-in-1 and 6-in-1 testing solutions. Testers include AC Hipot, DC Hipot, Ground Bond/Continuity, Insulation Resistance, Functional Run and Line Leakage tests. An optional internal scanner is available for the 8104, 4-in-1 tester. An additional external modular scanner is available for use with all testers. All testers come standard with USB and RS-232 interfaces. Ethernet, GPIB, and RS-485 interfaces are also available.

Model 8104 - OMNIA 4, 5kV @ 40mA AC, 5kV @ 20mA DC, IR Test, 40 Amp Ground Bond & Optional HV & HC Scanner

Model 8105 - OMNIA 5, 5kV @ 40mA AC, 5kV @ 20mA DC, IR Test, 40 Amp Ground Bond & Functional Run Test

Model 8106 - OMNIA 6, 5kV @ 40mA AC, 5kV @ 20mA DC, IR Test, 40 Amp Ground Bond, Functional Run Test & Line Leakage Test

Features and Benefits

- Patented SmartGFI® safety circuit protects the operator from shock hazards
- Real Current measurement allows operators to monitor total and real current on a single screen
- Patented Prompt and Hold function provides a unique method for performing multiple steps during a test cycle
- Line Leakage tester with 7 different measuring devices and RMS or PEAK leakage measurements
- Can be easily connected to AR's SC6540, 620L or an APT Brand AC Power Source to provide a customizable test system
- USB/RS-232, GPIB, Ethernet, or RS-485 automation interfaces available
- Autware Testing Software available for complete Automation Control
- Cold Resistance Feature for Line to Neutral Continuity Testing
- Patented CAL-ALERT® and VERI-CHEK® features help to ensure that your instrument is calibrated and stays within specs
- Data storage card available for storing and transferring test data without a connection to a PC
- 50 Memories with 30 steps per memory that can be stored and recalled in any alphanumeric combination
- RAMP HI® and CHARGE LO® testing for more effective DC Hipot testing
- Perform Hipot/Line Leakage without changing test leads
- Patented Graphic LCD and intuitive menu system to simplify the entire testing process from set-up to results

U.S. Patents: 6,744,259, 6,549,385, 6,515,484
6,054,865, 6,011,398, 5,936,419.
Other patents pending.



APT
AC Power Source
Compatible

www.aspowertechnologies.com



Safety agency listed.

Input Specifications

Voltage	115/230 V selectable, $\pm 10\%$ variation
Frequency	50/60 Hz $\pm 5\%$
Fuse	10A Slow-Blo 250VAC

Dielectric Withstand Test Mode

Output Rating	5 KV @ 40 mA AC 5 KV @ 20 mA DC
Voltage Setting	Range: 0-5000 V AC 0-5000 V DC Resolution: 1 V Accuracy: $\pm (2\% \text{ of setting} + 5 \text{ volts})$
Voltage Display	Range: 0.00 - 5.00KV Full Scale Resolution: 0.01 KV Accuracy: $\pm (2\% \text{ of reading} + 10 \text{ volts})$
HI and LO-Limit	AC Total Range: 0.000-9.999 mA Resolution: 0.001 mA Range: 10.00 – 40.00 mA Resolution: 0.01 mA Accuracy: $\pm (2\% \text{ of setting} + 2 \text{ counts})$ AC Real Range: 0.000-9.999 mA Resolution: 0.001 mA Range: 10.00 – 40.00 mA Resolution: 0.01 mA Accuracy: $\pm (3\% \text{ of setting} + 50\mu\text{A})$ DC Range: 0.0-999.9 μA Resolution: 0.1 μA Range: 1000 – 20000 μA Accuracy: $\pm (2\% \text{ of setting} + 2 \text{ counts})$
Current Display	AC Total Range: 0.000 mA – 3.500 mA Resolution: 0.001 mA Range: 3.00 mA – 40.00 mA Resolution: 0.01 mA Accuracy: $\pm (2\% \text{ of reading} + 2 \text{ counts})$ AC Real Range: 0.000 mA – 9.999 mA Resolution: 0.001 mA Range: 10.00 mA – 40.00 mA Resolution: 0.01 mA Accuracy: $\pm (3\% \text{ of reading} + 50\mu\text{A})$ DC Range: 0.0 μA – 350.0 μA Resolution: 0.1 μA Range: 0.300 mA – 3.500 mA Resolution: 0.001 mA Range: 3.00 mA – 20.00 mA Resolution: 0.01 mA Accuracy: $\pm (2\% \text{ of reading} + 2 \text{ counts})$
Ramp HI	>20 mA peak maximum, ON/OFF selectable
Charge LO	Range: 0.000 - 350 μA or Auto Set
DC Output Ripple	$\leq 4\%$ Ripple RMS at 5 KV DC @ 20 mA, Resistive Load
Discharge Time	$\leq 200 \text{ ms}$

Dielectric Withstand Test Mode (continued)

Max Capacitive Load	1 $\mu\text{F} < 1 \text{ KV}$ 0.08 $\mu\text{F} < 4 \text{ KV}$
DC Mode	0.75 $\mu\text{F} < 2 \text{ KV}$ 0.04 $\mu\text{F} < 5 \text{ KV}$ 0.5 $\mu\text{F} < 3 \text{ KV}$
AC Output Waveform	Sine Wave, Crest Factor = 1.3 - 1.5
Output Frequency	60 or 50 Hz, User Selectable
Output Regulation	$\pm (1\% \text{ of output} + 5 \text{ V})$ from no load to full load and over input voltage range
Dwell Timer	AC 0.4 - 999.9 sec (0 = Continuous) DC 0.3 - 999.9 sec (0 = Continuous)
Ramp Timer	Ramp-Up: AC 0.1 - 999.9 sec, DC 0.4 - 999.9 sec Ramp-Down: AC 0.0 - 999.9 sec, DC 0.0, 1.0 - 999.9 sec
Ground Continuity	Current: DC 0.1 A $\pm 0.01 \text{ A}$, fixed Max. Ground Resistance: 1 $\Omega \pm 0.1 \Omega$, fixed
Ground Fault Interrupt	GFI Trip Current: 450 μA max (AC or DC) HV Shut Down Speed: < 1 ms

Continuity Test Mode

Output Current	DC 0.1 A $\pm 0.00001 \text{ A}$
Resistance Display	Range: 0.00 – 10000.00 Ω
HI and LO-Limit	0.00 – 10000 Ω
Dwell Timer	Range: 0.0, 0.3 - 999.9 sec (0 = Continuous)
Milliohm Offset	Range: 0.00 – 10.00 Ω

Ground Bond Test Mode

Output Voltage	Range: 3.00 - 8.00 VAC
Output Frequency	50/60 Hz, user selectable
Output Current	Range: 1.00 - 40.00 A, Resolution: 0.01 A
Output Regulation	Accuracy: $\pm (1\% \text{ of output} + 0.02 \text{ A})$ Within maximum load limits, and over input voltage range
Maximum Loading	1.00 - 10.00 A, 0 - 600 m Ω 10.01 - 30.00 A, 0 - 200 m Ω 30.01 - 40.00 A, 0 - 150 m Ω
Current display	Range: 0.00 – 40.00 A Resolution: 0.01 A Accuracy: $\pm (3\% \text{ of setting} + 0.03 \text{ A})$
Ohmmeter Display	Range: 0 – 150 m Ω for 30.01 – 40.00 Amps 0 – 200 m Ω for 10.01 – 30.00 Amps 0 – 600 m Ω for 6.00 – 10.00 Amps Resolution: 1 m Ω Accuracy: $\pm (2\% \text{ of reading} + 2 \text{ m}\Omega)$ Range: 0 – 600 m Ω for 1.00 – 5.99 Amps Resolution: 1 m Ω Accuracy: $\pm (3\% \text{ of reading} + 3 \text{ m}\Omega)$

Ground Bond Test Mode (continued)

HI and LO Limit	Range: 0 – 150 mΩ for 30.01 – 40.00 Amps 0 – 200 mΩ for 10.01 – 30.00 Amps 0 – 600 mΩ for 1.00 – 10.00 Amps Resolution: 1 mΩ Accuracy: Same as Ohmmeter Display
Milliohm Offset	Range: 0 - 200 mΩ

Insulation Resistance Test Mode

Voltage Setting	Range: 50 - 1000 VDC
Charging Current	Maximum >20 mA peak
Resistance Display	Range: 0.05 MΩ – 50000 MΩ (4 Digit, Auto Ranging) Resolution: 50 – 499 VDC 500 – 1000 VDC MΩ MΩ MΩ 0.001 0.050 – 1.999 0.050 – 9.999 0.01 2.00 – 19.99 10.00 – 99.99 0.1 20.0 – 199.9 100.0 – 999.9 1 200 – 50000 1000 – 50000
Accuracy	50 – 499 V 0.05 M – 999.9 M, ± (7% of reading +2 counts) 500 – 1000 V 0.05 M – 999.9 M, ± (2% of reading +2 counts) 1000 M – 9999 M ± (5% of reading +2 counts) 10000 M – 50000 M, ± (15% of reading +2 counts)
HI and LO Limit	Range: 0.05 M – 99.99 MΩ Resolution: 0.01 M Range: 100.0 M – 999.9 M Resolution: 0.1 M Range: 1000 M – 50000 M Resolution: 1 M (HI – Limit: 0 = OFF) Accuracy: Same as Resistance Display Accuracy
Charge LO	Range: 0.000 - 3.500 μA or Auto Set
Ramp Timer	Ramp-Up: 0.1 - 999.9 sec Ramp-Down: 0.0, 1.0 - 999.9 sec
Delay Timer	1.0 - 999.9 sec (0 = Continuous)
Ground Fault Interrupt	GFI Trip Current: 450 μA max (AC or DC) HV Shut Down Speed: < 1 ms

General Specifications

Mechanical	Bench or rack mount with tilt up front feet
Dimensions	3U (WxHxD) 16.93 x 5.24 x 19.69 in. (430 x 133 x 500 mm)
Weight	8104 - 26 kgs / 57.32 lbs. 8105/8106 - 29 kgs. / 63.93 lbs.
Interface	USB/RS-232 Standard, GPIB, Ethernet, Data Storage (RS-485)
Memory	50 memories, 30 step/memory

OMNIA 8105 and 8106 Functional Run Test Mode

DUT Power	Voltage: 0 – 277 VAC Single Phase Unbalanced (One Hot or Line conductor and One Neutral) Current: 15 AAC max continuous Short Circuit Protection: 23 AAC, Response Time < 3s
Delay Time Setting	Range: 0.2 – 999.9 seconds
Dwell Time Setting	Range: 0.1 – 999.9 seconds (0 = Continuous)
Trip Point Settings	Voltage: Volt-Hi Volt-LO Range: 0.0 – 277.0 VAC Current: Amp-Hi Amp-LO Range: 0.0 – 15.00 AAC Watts: Power-Hi Power-LO Range: 0 – 4200 W Power Factor: PF-Hi PF-LO Range: 0.000 – 1.000 Leakage Current: Leak-Hi Leak-LO Range: 0.00 – 10.00 mA (0 = OFF)

OMNIA 8106 Line Leakage Test Mode

DUT Power	Voltage: 0 – 277 VAC Current: 15 AAC max continuous Short Circuit Protection: 23 AAC, Response Time <3s
Leakage Current	Current Display RMS or PEAK Range 1: 0.0 μA – 999.9 μA Resolution: 0.1 μA/step Range 2: 1000 μA – 6000 μA Resolution: 1 μA/step Accuracy RMS: DC to 100 kHz ± (1.5% of reading +3 counts) >100k to 1 MHz ± 5% of reading, (10.0 μA – 6000 μA)
Measuring Device	A UL544 Non Patient B UL544 Patient C UL2601-1, UL60601-1, IEC601-1, IEC60601-1 EN60601-1 D UL1563 E UL1950, UL3101, UL61010, IEC950, IEC1010, IEC60950, IEC61010, IEC60335-1, IEC60990 Fig4-U2 H IEC60990 Fig5-U3 I IEC60990 Fig3-U1

We have local sales offices throughout the world to serve you more efficiently.

To find your nearest representative visit the "Local Sales Offices" section of our web site at www.asresearch.com or call us toll-free at 1-800-858-8378

Distribido Por:
www.finaltest.com.mx
Calle del Ebano #16625
Tijuana B.C. Mexico
Tel. (664)681-1130
Tel. 01800 027-4848
ventas@final-test.net



13860 West Laurel Drive,
Lake Forest, IL U.S.A. 60045

Tel: +1-847-367-4077 Fax: +1-847-367-4080

E-mail: info@asresearch.com

For more information visit us at www.asresearch.com
or call us toll-free at 1-800-858-TEST(8378)